

6877-1 Goreway Drive
Mississauga, Ontario
Canada L4V 1L9

Tel: (905) 677-5533
Fax: (905) 677-5030
web: www.rmsinst.com
e-mail rms@rmsinst.com

POWER DISTRIBUTION UNIT



Reliable power distribution for equipment racks, ensuring that your installation performs up to the standards demanded by your unique application requirements.

SPECIFICATIONS	
Outputs:	6 x 28VDC at 5-Amp—individual circuit breaker protection for each load, (J1—J6) 2 x 28VDC at 10-Amp—individual circuit breaker protection for each load, (J7—J8) (PT02E12-3S 3-pin connectors) 2 x 12VDC regulated output 6-Amp load on each 4-pin connectors (206430-1), (J10, J11)
Inputs:	50 Amp protected—practical load is 45 Amps @ 28VDC input, (MS3102E-22-22P), (J9)
Pilot Control/Shut off:	Pilot control shut off connector (PT02A8-4S) - pins A and D shorted to activate relay, (J12)
Front Panel Indicators:	On/Off switch Lamp aircraft voltage source input indicator (power) Digital meter, switch selectable between voltage and current
Size:	1.75" x 19.0" x 13.0" (4.5 x 48.3 x 33.0 cm)
Weight:	8 pounds (3.6 Kg)
Operating Temperature:	0 to 50°C
Storage Temperature:	-20 to 55°C