



RMS INSTRUMENTS

For Geophysical Exploration

6877-1 Goreway Drive
Mississauga, Ontario
Canada, L4V-1L9

Tel: (905) 677-5533
Fax: (905) 677-5030
e-mail: rms@rmsinst.com
<http://www.rmsinst.com>

RELEASE NOTES

AARC510 Adaptive Aeromagnetic Real-Time Compensator

Host Firmware Release RMS11031-01-F

These release notes contain important information about the new firmware and how it will affect the performance of instruments in which it is installed. The notes outline functional enhancements, adaptive changes and, if applicable, problem corrections.

Please read this documentation carefully. References to pertinent sections in the product's user's guide are shown in square brackets.

Compatibility:

(D)AARC500 Front End – Requires firmware RMS1877-04-A or later

1. The firmware supports a new Front End transfer function, 'Custom2', which the user may customize to the requirements of a specific airborne installation.
[User's Guide: Sections 3.4.1.1c and 4.3]
2. The firmware supports the new gating signal for qualification of magnetometer readings, implemented through the Front End. This functionality is intended for use of the AARC510 in installations running EM systems concurrently with the magnetics.
[User's Guide: Sections 4.3.2 and 2.3.12]
3. Additional information is now recorded in the 'monasc.txt' logging file to provide more comprehensive records of each mission.